



TYPICAL SECTION

NOTES:

1. STRUCTURAL SECTION OF ROADWAY SHALL BE DETERMINE FROM SOILS REPORT, TRAFFIC INDEX, AND STREET DESIGNATION, PREPARED BY SOILS ENGINEER PRIOR TO FINAL APPROVAL OF IMPROVEMENT PLANS. MINIMUM STRUCTURAL SECTION PER CITY STANDARD 90 SHALL PREVAIL.
2. CURB RETURNS AT LOCAL PUBLIC STREETS SHALL HAVE A RADIUS EQUAL TO 20 FEET UNLESS OTHERWISE APPROVED BY THE CITY ENGINEER.
3. AC OVERLAY AND FINISH COURSES SHALL BE 0.1-FT. MINIMUM IN THICKNESS, D2-PG 64-10 OR D2-PG 64-10 RAP. BASE COURSES SHALL BE MINIMUM 0.15', C2-PG 64-10 OR C2-PG 64-10 RAP UNLESS OTHERWISE APPROVED BY THE CITY ENGINEER.

APPR. BY:  07/11
 STEVEN C. NIX, CITY ENGINEER DATE

CITY OF CHINO HILLS
 ENGINEERING DEPARTMENT

DATE	REVISION	BY

LOCAL STREET - PUBLIC

105